

DISCONTINUED PRODUCT



GALERIE SMOOTH GLOSS PRE-MOUNTED BOARDS (IGSGP9)

Instant dry is now a standard requirement for many professional users of inkjet media. GALERIE Smooth Gloss has high gloss finish to give stunning results that have the look and feel of real photographs. The unique range of pre-mount media can be fed directly through the Epson® 9000, 7000, 4000 and 2000 Series printers giving prints straight from the printer, ready to frame.

- Photo gloss surface
- Instant dry porous surface (more information)
- Superb photographic image quality and consistency

Technical Specification	Sheets
Weight	1100gsm
Caliper	1300 microns (52mil)
Gloss (20°)	>42%
Tint (lab)	96.0, 0.2, -4.7

For optimum image stability, use with pigment-based inks.

DISCONTINUED PRODUCT



INKJET MEDIA NOTES

DRYING

Porous media: (Smooth)

Although instant dry porous coated media is touch-dry straight out of the printer, it is recommended that prints are left to dry fully before laminating. As with other inkjet papers, it is recommended that media is left for 24 hours for consistent results.

Polymer (swellable) media: (Classic)

As with other aqueous inkjet papers, 24 hours drying time should be allowed for consistent results and before lamination to allow the print to fully dry.

IMAGE STABILITY/FADE RESISTANCE

Image stability is highly dependent on the ink in your printer. Please check printer manufacturer for specific performance details.

IMAGE QUALITY AND CONSISTENCY

As with all porous ('Instant' dry) coated media, ILFORD GALERIE Smooth Paper can be susceptible to 'gas fading' due to airborne pollutants. Covering the image with glass for example, will ensure that a print from a dye based printer will last for up to 10 years depending on the manufacturer's ink. Initial accelerated testing indicates that a GALERIE Smooth Paper product will last in excess of 30 years using a pigment ink desktop printer.

IMAGE QUALITY ON HIGH GLOSS AND GLOSS MEDIA

For optimum quality when using high gloss or gloss media the use of dye inks are recommended. If pigment inks are used they may lead to a matting of the surface in areas of high ink load. Some printers allow the use of gloss optimisers that can reduce this effect. ILFORD has in the design of its ICC profiles endeavoured to optimise the balance of image quality and surface gloss

SMOOTH GLOSS PRE-MOUNTED BOARDS

IGSGP9

ILFORD GALERIE Smooth Gloss is a premium RC paper, designed to deliver the best in professional photographic digital prints. It incorporates an advanced nanoporous receiving layer for instant drying and outstanding image quality. ILFORD GALERIE Smooth Gloss media is custom laminated using acid free materials to ensure excellent archival properties. The unique range of pre-mount media can be fed directly through the Epson® 9000, 7000, 4000 and 2000 Series printers giving prints straight from the printer, ready to display.

FEATURES

- Market leading gloss media, the surface that professionals prefer
- Outstanding photographic image quality and consistency, even at the fastest print speeds
- Excellent smudge and water resistance
- Pre-mounted board for easy post print handling/finishing

PRINTER & INK COMPATIBILITY

Designed for use with most wide format inkjet printer systems using pigment inks from major manufacturers.

AVAILABILITY

ILFORD GALERIE Smooth Gloss is available in over-size pre-mounted boards. For more details, please see the Availability Chart in the GALERIE section of www.ilford.com

PHYSICAL PROPERTIES (TARGET VALUES)

Pre-mount Media

Weight: 1100gsm

Caliper: 1300microns (52mil)

Tint (Lab): 96.0, 0.2, -4.7

Gloss (20°): >42%

ENVIRONMENTAL CONDITIONS

Operating: 15–25°C, 40–60% r.h. non-condensing

Storage: 15–25°C, 30–70% r.h. non-condensing

HANDLING & STORAGE

Store pre-mounted boards horizontally to prevent curl.

Note: Specifications subject to change without notice.
All trademarks are the property of their respective companies.